






757-842-6497
WWW.JLOSC.COM

**J&L 3.0 Oil Separator (2015-2025 Transit 150/250/350 3.5 EcoBoost Passenger side)
#3025P
Installation Instructions**

Please review complete instructions prior to installing.

Step #	
1	Verify you have all of the following parts included in the kit: (1) J&L Oil Separator, (1) Mounting bracket, (2) Fine thread screws, (1) M6 Bolt
2	Gather all of the following tools needed for the installation: 10mm Socket, 13mm Socket, Extension, ratchet and Phillips screwdriver
3	Remove factory PCV Line here, pull Grey/Blue tab away from fitting and pull assembly outward. 
4	Remove 13mm ball stud from passenger side valve cover.



5 Use supplied screws to mount the bracket onto the Oil Separator, align logos so they match the same direction.

Mount the oil separator and bracket to valve cover using the J&L supplied bolt.

Connect long hose to intake manifold fitting, connect short hose to PCV connection on valve cover.

TIP: The quick connect fittings in the end of the rubber hose will rotate 360 degrees, if the fitting needs adjustment for optimal fitment just twist the fitting!

6

Check the oil separator 1000 miles after installation to get a better idea of how frequently you will need to empty it. This kit is compatible with our 3oz reservoir extension (Part numbers# EXT-B , EXT-C)



To properly clean the filter in the Oil Separator, spray any degreaser or solvent through it and let it air dry. Clean it every 10,000 miles.

Thank you for your business. If you have any questions, please e-mail info@JLosc.com or call 757-842-6497. Our hours are Monday-Friday, 8:00am – 4:30pm Eastern Time.

J&L Oil Separator co. Lifetime Satisfaction Guarantee. We want you to be a J&L customer for life! Your new J&L product is warranted to be free from defects in materials and workmanship for the life of the *original retail purchaser*, subject to the limitations contained in our warranty found here. www.JLosc.com/warranty

We guarantee workmanship and even a pathway to discounted upgrades for substantially improved items.

Return Policy: All returns will be subject to a 10%-25% restocking fee. Please visit www.JLosc.com for complete return policy.

Disclaimer: J&L Oil Separator co. makes no warranties whatsoever, expressed, or implied, oral or written to any purchasers, except the warranty above. J&L Oil Separator co. hereby specifically excludes from any implied warranty of merchantability or implied warranty of incidental, secondary, or consequential damages of any kind whatsoever. All purchasers and users of products manufactured by J&L Oil Separator co. agree to hold harmless and indemnify J&L Oil Separator co. from any and all claims arising from their use. Failure to receive notice of any or the limitations contained in this disclaimer shall not serve to extend liability to J&L Oil Separator co. for any claims arising out of use of its products.