



**757-842-6497**  
**WWW.JLOSC.COM**

## J&L 3.0 Oil Separator (2017-19 Ford Fusion Sport EcoBoost 2.7L V6 Passenger Side) #3034P

### Installation Instructions

Install video available on our website [www.JLosc.com](http://www.JLosc.com) Search: 3034P and click videos

Please review complete instructions prior to installing.

Step#	
1	<b>Verify you have all of the following parts included in the kit:</b> (1) J&L Oil Separator, (1) J&L Mounting bracket, (2) Fine thread machine screws, (1) Mounting Bolt
2	<b>Gather all of the following tools needed for the installation:</b> 8mm wrench, 10mm socket, extension and ratchet, & Phillips screwdriver
3	Remove engine cover by removing 10mm Bolt and 10mm nut. Pull up on engine cover to release.
4	Remove factory PCV line by pulling tabs and pulling it off of the engine. 
5	Locate 8mm bolt that holds a bracket on the passenger side of the engine and remove bolt. Install J&L Bracket in the same location and reinstall bolt. You can either reuse factory bolt or supplied bolt with kit. 

Install J&L can onto J&L bracket using the two supplied screws. Route short hose to PCV valve on valve cover (90° fitting), sweep longer hose and hook to intake manifold (45° fitting)



Reinstall engine cover and you're done!

**To service can-** you will need to remove the can from the vehicle as this engine bay is very tight on space.

To remove fittings, press large grey button inward to release and pull upward on fitting. You do not need to remove the grey clips from the fittings.

6

To properly clean the filter in the Oil Separator, spray any degreaser or solvent through it and let it air dry. Clean it every 10,000 miles.

Thank you for your business. If you have any questions, please e-mail [info@JLosc.com](mailto:info@JLosc.com) or call 757-842-6497. Our hours are Monday-Friday. 8:00am – 4:30pm Eastern Time.

**J&L Oil Separator co. Lifetime Satisfaction Guarantee. We want you to be a J&L customer for life!** Your new J&L product is warranted to be free from defects in materials and workmanship for the life of the *original retail purchaser*, subject to the limitations contained in our warranty found here. [www.JLosc.com/warranty](http://www.JLosc.com/warranty)

We guarantee workmanship and even a pathway to discounted upgrades for substantially improved items.

**Return Policy:** All returns will be subject to a 10%-25% restocking fee. Please visit [www.JLosc.com](http://www.JLosc.com) for complete return policy.

**Disclaimer:** J&L Oil Separator co. makes no warranties whatsoever, expressed, or implied, oral or written to any purchasers, except the warranty above. J&L Oil Separator co. hereby specifically excludes from any implied warranty of merchantability or implied warranty of incidental, secondary, or consequential damages of any kind whatsoever. All purchasers and users of products manufactured by J&L Oil Separator co. agree to hold harmless and indemnify J&L Oil Separator co. from any and all claims arising from their use. Failure to receive notice of any or the limitations contained in this disclaimer shall not serve to extend liability to J&L Oil Separator co. for any claims arising out of use of its products.