




**757-842-6497**  
**WWW.JLOSC.COM**

**J&L Oil Separator, Passenger Side (2011-2023 3.6L Charger, Challenger, 300c)  
#3068P**

**Installation Instructions**

**Check out the install video of this product on our website [www.JLosc.com](http://www.JLosc.com) Search: 3068P and click videos**

**Please review complete instructions prior to installing.**

Step#	
<b>1</b>	<b>Verify you have all of the following parts included in the kit:</b> (1) J&L Oil Separator, (1) J&L Mounting bracket, (2) M4 screws, (1) M6 Nut (10mm)
<b>2</b>	<b>Gather all of the following tools needed for the installation:</b> 10mm & 13mm sockets, ratchet, Phillips screwdriver, flat head screwdriver, pliers
<b>3</b>	<p>Remove the factory engine cover by pulling up at corners of cover. Remove factory PCV hard line from vehicle. You will need to break the seal of the rubber coupler and plastic line. You can use a small flathead screwdriver to separate the rubber from the plastic. On the manifold side remove entire assembly from vehicle to work with it off the car.</p> <p>Reinstall rubber coupler onto the intake manifold.</p> 

Remove 13mm nut on shock tower. Install J&L bracket over stud and J&L supplied nut(10mm).



4

Use the supplied screws and mount the Oil Separator to the J&L bracket. Route hoses to their proper PCV connections. Plug in connections to rubber couplers on vehicle. Reinstall the engine cover.

5



To properly clean the filter in the Oil Separator, spray any degreaser or solvent through it and let it air dry. Clean it every 10,000 miles.

Thank you for your business. If you have any questions, please e-mail [info@JLosc.com](mailto:info@JLosc.com) or call 757-842-6497. Our hours are Monday-Friday. 8:00am – 4:30pm Eastern Time.

**J&L Oil Separator co. Lifetime Satisfaction Guarantee.** We want you to be a J&L customer for life! Your new J&L product is warranted to be free from defects in materials and workmanship for the life of the *original retail purchaser*, subject to the limitations contained in our warranty found here. [www.JLosc.com/warranty](http://www.JLosc.com/warranty)

We guarantee workmanship and even a pathway to discounted upgrades for substantially improved items.

**Return Policy:** All returns will be subject to a 10%-25% restocking fee. Please visit [www.JLosc.com](http://www.JLosc.com) for complete return policy.

**Disclaimer:** J&L Oil Separator co. makes no warranties whatsoever, expressed, or implied, oral or written to any purchasers, except the warranty above. J&L Oil Separator co. hereby specifically excludes from any implied warranty of merchantability or implied warranty of incidental, secondary, or consequential damages of any kind whatsoever. All purchasers and users of products manufactured by J&L Oil Separator co. agree to hold harmless and indemnify J&L Oil Separator co. from any and all claims arising from their use. Failure to receive notice of any or the limitations contained in this disclaimer shall not serve to extend liability to J&L Oil Separator co. for any claims arising out of use of its products.